



GENERAL NOTES

1. REFER TO A601 FOR DOOR INFORMATION & A602 FOR STOREFRONT DIMENSIONS.
2. ALL DIMENSIONS ARE TO FACE OF WALL SHEATHING, FACE OF STOREFRONT, OR CENTERLINE OF STRUCTURE UNLESS NOTES OTHERWISE.
3. SEE STRUCTURAL SHEETS FOR EXTERIOR WALL FRAMING AND SHEATHING.
4. ALL EXTERIOR WOOD BLOCKING TO BE MOISTURE RESISTANT PRESERVATIVE TREATED (P.T.).
5. TAPE SEALANT AT ALL ANCHOR LOCATIONS.
6. ALL FLASHING AND SEAMS BETWEEN SHEATHING IN COMPOSITE WOOD STUD WALL CONSTRUCTION CONDITIONS TO BE TAPED AND SEALED WITH TAPE SEALANT.
7. LAP ALL WEATHER RESISTANT BARRIERS AND THRU-WALL FLASHING IN A WATER SHEDDING FASHION, TAPE ALL EXPOSED EDGES.
8. EXTEND ALL THRU-WALL FLASHING TO 1/4 INCH PAST THE EXTERIOR FACE OF WALL. PROVIDE CONTINUOUS ANCHORAGE FOR ALL THRU-WALL FLASHING.
9. EXTEND FLASHING VERTICALLY A MINIMUM OF 6 INCHES ABOVE THE BASE OF THE FLASHING.
10. APPLY SEALANT TO ALL SHEATHING JOINTS AND FASTENER PENETRATIONS.
11. PROVIDE FULLY ADHERED FLASHING AT ALL WINDOW AND DOOR OPENING HEADS, SILLS AND JAMBS.
12. EDGE OF SLAB/CURB ALIGNS WITH EXTERIOR FACE OF WALL SHEATHING AND EXTERIOR FACE OF STOREFRONT.

LEGEND

- 2x6 WOOD STUD WALL WITH R-21 THERMAL BATT INSULATION
- DOOR TYPE, RE: A601
- STOREFRONT TYPE, RE: A602

JOHN M DUNGAN
ARCHITECT

8826 Santa Fe Drive
Suite 304
Overland Park, KS 66212

913-341-2466
913-341-2455 fax

COPYRIGHT 2022
THIS DRAWING IS AN INSTRUMENT OF SERVICE,
AND AS SUCH, REMAINS THE PROPERTY OF
DUNGAN DESIGN GROUP, LLC. PERMISSION FOR
USE OF THIS DOCUMENT IS LIMITED AND CAN BE
EXTENDED ONLY BY WRITTEN AGREEMENT WITH
DUNGAN DESIGN GROUP, LLC.

Shell Building

57552-57672 Twentynine Pines Hwy
Yucca Valley, CA 92284

Issue Record:

mm/dd/yy	Permit Issue

Revisions:

Project No:
01612

Architectural Shell
Floor Plan